



AYAA TECHNOLOGY CO.,LTD
PCM Specifications

Model: PCM-L02S30-A89

Test item (Test at normal temperature 25±2°C)		Criterion
Voltage	Charging voltage	DC: 8.4V CC/CV (4.2v/Cell) 2s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD >Sleep Current	≤30uA
	Maximal continuous charging current	30A
	Maximal continuous discharging current	30A
	Balance current for single cell	42±10mA
Over charge Protection (single cell)	Balance voltage for single cell	4.20±0.05V
	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.05±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.4±0.05V
	Over discharge detection delay time	10—200mS
	Over discharge release voltage	3.0±0.1V
current protection (Battery pack)	Discharge Over current detection current	100±20A
	Detection delay time	5ms—60ms
	Release condition	Cut load,Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤60mΩ
Temperature	Operating Temperature Range	-40~+85°C
	Storage Temperature Range	-40~+125°C
SIZE: L120*W35*T6.5 mm		
NTC: / Temperature switch: / Weak current switch: / Activation Method:/		
		