



**AYAA TECHNOLOGY CO.,LTD**  
**PCM Specifications**

**Model: PCM-LI05S8-002**

Test item (Test at normal temperature 25±2°C )		Criterion
Voltage	Charging voltage	DC: 17.25V~21V CC/CV (3.45V~4.2V/Cell) 5s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD >Sleep Current	≤30uA
	Maximal continuous charging current	4-7A
	Maximal continuous discharging current	4-7A
Over-charge Protection (single cell)	Over charge detection voltage	3.65-4.35V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.05-4.15V
Over discharge protection (single cell)	Over discharge detection voltage	2.4-3.0V
	Over discharge detection delay time	10—200mS
	Over discharge release voltage	2.5-3.2V
Current protection (Battery pack)	Discharge Over current detection current	12-21A
	Detection delay time	5ms—20ms
	Release condition	Cut load, Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤65mΩ
Temperature	Operating Temperature Range	-40～+85°C
	Storage Temperature Range	-40～+125°C

SIZE: L85.3 \*W16 \*T2.8 mm

NTC: /      Temperature switch: /      Weak current switch: /      Activation Method:/

