




AYAA TECHNOLOGY CO.,LTD
PCM Specifications

Model: SH18650B (LI 1S8A) R5478N101CD+8810*3		Ver: A
Test item (Test at normal temperature 25±2℃)		Criterion
Voltage	Charging voltage	DC: 4.2V CC/CV (4.2V/Cell) 1s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD > Sleep Current	≤7uA
	Maximal continuous charging current	8A
	Maximal continuous discharging current	8A
Over-charge Protection (single cell)	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.05±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.5±0.05V
	Over discharge detection delay time	10—200mS
	Over discharge release voltage	3.0±0.1V
Current protection (Battery pack)	ChargeOver current detection current	/
	Detection delay time	/
	Discharge Over current detection current	20±5A
	Detection delay time	5ms—20ms
	Release condition	Cut load, Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤65mΩ
Temperature	Operating Temperature Range	-40~+85℃
	Storage Temperature Range	-40~+125℃

SIZE: L18*W18*T2 mm

NTC: / Temperature switch: / Weak current switch: / Activation Method: /



Prepared: Hardy 2017-8-28

Checked:

Approved: