



AYAA TECHNOLOGY CO.,LTD  
PCM Specifications

Model: PCM-Li4S5-068

Test item (Test at normal temperature 25±2℃)		Criterion
Voltage	Charging voltage	DC: 50.4V CC/CV (4.2v/Cell) 12s
Supply Current	Normal operating mode current: Fuel gauge in NORMAL mode. ILOAD > Sleep Current	≤20uA
	Maximal continuous charging current	4A
	Maximal continuous discharging current	4A
	Balance current for single cell	/
Over charge Protection (single cell)	Balance voltage for single cell	/
	Over charge detection voltage	4.25±0.05V
	Over charge detection delay time	0.5S—2S
	Over charge release voltage	4.15±0.1V
Over discharge protection (single cell)	Over discharge detection voltage	2.7±0.05V
	Over discharge detection delay time	10—200mS
	Over discharge release voltage	3.0±0.1V
current protection (Battery pack)	Discharge Over current detection current	10±3A
	Detection delay time	5ms—50ms
	Release condition	Cut load, Auto Recovery
Short protection	Detection condition	Exterior short circuit
	Detection delay time	200-600us
	Release condition	Cut load
Resistance	Main loop electrify resistance	≤20mΩ
Temperature	Operating Temperature Range	-40~+85℃
	Storage Temperature Range	-40~+125℃

SIZE: L26 \*W26 \*T3 mm

NTC: / Temperature switch: / Weak current switch: / Activation Method: /

